

COMPACT 5000 SERIES

Fire tested to BS476 Part 20



Cash Rating £5,000
Jewellery Rating £50,000

A range of safes available in 4 sizes, suitable for domestic and medium commercial applications.

Body Thickness is 50mm with an 83mm overall thickness door.

Boltwork is 4-way engaged (3-way moving) with 28mm dia. bolts.

Fire tested to BS476 Part 20.

Supplied as standard keylock (certified to EN1300) with two keys, base fixing and one adjustable shelf.

Locking options include: Keyless combination; electronic combination and the facility for dual locking if required, time locks and time delay locks.

SIZE	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	KGS	VOL
	H x W x D (mm)	H x W x D (mm)		
Com 0	412 x 379 x 359 mm	312 x 279 x 222 mm	100	19
Com 1	481 x 430 x 429 mm	381 x 330 x 292 mm	158	36.5
Com 2	605 x 430 x 429 mm	508 x 330 x 292 mm	173	49
Com 3	532 x 532 x 559 mm	432 x 432 x 432 mm	200	80.5

Please note that external depths do NOT include handle and hinges (please allow an extra 65mm). All weights and sizes are approximate.

Dudley Safes Ltd. reserve the right to change specifications without notice.

freephone: 08006 121 160
fax: 01527 451387
e-mail: info@first4safes.co.uk

www.first4safes.co.uk